

# C104H/HS

## 4-port RS-232 ISA serial boards



PCComm Lite

- > Cost-effective, compact ISA boards with 4 RS-232 ports
- > 921.6 kbps maximum baudrate for super fast data transmission
- > 16-byte FIFO and on-chip H/W, S/W flow control
- > Drivers provided for Windows, Windows XP Embedded, DOS, Linux 2.4, Linux 2.6, QNX 4/6, FreeBSD, SCO OpenServer, UnixWare 7, Solaris 10
- > Easy configuration, without switches or jumpers



12

Multiport Serial Boards > C104H/HS

### Overview

The 4-port C104H/HS ISA boards offer users an economical, high performance multiport serial communication solution for connecting terminals, modems, printers, data acquisition equipment, and other serial devices to a PC. The boards are a top choice of industrial

automation engineers and system integrators, and support many different operating systems, including Windows, Linux, and even Unix. In addition, each of the 4 RS-232 ports supports a super fast 921.6 kbps baudrate.

### Specifications

#### Hardware

**Comm. Controller:** 16C550C or compatible x 4

**Bus:** 16-bit ISA

**Connector:** DB37 female

#### Serial Interface

**Number of Ports:** 4

**Serial Standards:** RS-232

**Max. No. of Boards per PC:** 4

#### Serial Line Protection

**ESD Protection:** 25 kV on the board (C104HS only)

#### Performance

**Baudrate:** 50 bps to 921.6 kbps

#### Serial Communication Parameters

**Data Bits:** 5, 6, 7, 8

**Stop Bits:** 1, 1.5, 2

**Parity:** None, Even, Odd, Space, Mark

**I/O Address:** 0x0000-0xFFFF (default = 0x180)

**IRQ:** 2 (9), 3, 4, 5, 7, 10 (default), 11, 12, 15

#### Serial Signals

**RS-232:** TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

#### Operating Systems

**Windows Real COM Drivers:** Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1 (x86/x64), Windows 2008 R2/2012/2012 R2 (x64), Windows 3.x, DOS, Windows Embedded CE 5.0/6.0, Windows XP Embedded

**Fixed TTY Drivers:** QNX 6, SCO OpenServer, UnixWare 7, Solaris 10, FreeBSD

**Linux Real TTY Drivers:** Linux 2.4.x, 2.6.x

*Note: Please refer to Moxa's website for the latest driver support information.*

#### Physical Characteristics

**Dimensions:** 83 x 157 mm (3.27 x 6.18 in)

#### Environmental Limits

**Operating Temperature:** 0 to 55°C (32 to 131°F)

**Storage Temperature:** -20 to 85°C (-4 to 185°F)

**Ambient Relative Humidity:** 5 to 95% (non-condensing)

**Altitude:** Up to 2000 m

*Note: Please contact Moxa if you require products guaranteed to function properly at higher altitudes.*

#### Standards and Certifications

**EMC:** CE, FCC

**EMI:** EN 55022, FCC Part 15 Subpart B Class A

**EMS:** EN 61000-4-2, EN 61000-4-3, EN 61000-4-4

**Green Product:** RoHS, CRoHS, WEEE

**MTBF** (mean time between failures)

**Time:** 629,545 hrs

**Database:** MIL-HDBK-217F, GB 25°C

#### Power Requirements

**Power Consumption:** 100 mA max. @ +5 V, 100 mA max. @ +12 V, 60 mA max. @ -12 V

#### Warranty

**Warranty Period:** 5 years

**Details:** See [www.moxa.com/warranty](http://www.moxa.com/warranty)

### Ordering Information

#### Available Models

**C104H:** 4-port RS-232 ISA serial board

**C104H-DB9M:** 4-port RS-232 ISA serial board (includes DB9 male cable)

**C104H-DB25M:** 4-port RS-232 ISA serial board (includes DB25 male cable)

**C104HS:** 4-port RS-232 ISA serial board with surge protection

**C104HS-DB9M:** 4-port RS-232 ISA serial board with surge protection (includes DB9 male cable)

**C104HS-DB25M:** 4-port RS-232 ISA serial board with surge protection (includes DB25 male cable)

#### Connection Options (can be purchased separately)

**CBL-M37M9x4-30:** DB37 male to DB9 male x 4 connection cable, 30 cm

**CBL-M37M25x4-30:** DB37 male to DB25 male x 4 connection cable, 30 cm

#### Package Checklist

- 1 C104H or C104HS board
- DB9 male or DB25 male connection cable
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card